



Plasma CUT 105

Our CUT105 is capable for cutting all metal material such as carbon steel, stainless steel, aluminum, brass and copper. The unique compact design allow user to have the option for accessories such as trolley, water tank and power source according to the application.

ADVANTAGES

- ✓ Compact Design
- ✓ Microprocessor Control
- ✓ Unique Air Duct Design
- ✓ Can be repaired in 10 minutes
- ✓ Manufacturing under (CE) Certificate

BASIC UNIT INCLUDE

- ✓ Earth Clamp c/w cable
- ✓ Air Regulator
- ✓ P80 Plasma Torch
- ✓ Owner Instruction Book

PARAMETERS

	Adjustment range	Preset
Input power voltage (V)	AC415V±15% 3PH	
Input voltage frequency (HZ)	50/60	
Rated input power capacity (KVA)	16.2	
No-load voltage (V)	285	
Output current range (A)	5-105	
Pre-flow(S)	0.1-5	1
Post-gas(S)	0-30	5
Motor generator requirements for full arc stretch at full output (KW)	30	
Duty cycle (%)	60	
Severance capacity(mm)	40	
Recommended cut capacity(mm)	30	
Weight (KG)	38	
Dimension (mm)	622×280×480	

Website: www.dynaweld.com.my

Email : marketing@dynaweld.com.my

Contact: +603-83227661

Fax : +603-83251665