



Plasma CUT 160

Our CUT160 is capable for cutting all metal material such as carbon steel, stainless steel, aluminum, brass and copper. the machine is packed with innovative unique features to provide more flexibility for the long cutting and install for automation cutting. The Easy Operationg Funtion, Its gine more flexibility for deference thickness of cutting application.

ADVANTAGES

- ✓ Compact Design
- ✓ Microprocessor Control
- ✓ The Unique Air Duct Design
- ✓ Unitization design
- ✓ Comprehensive protecting function
- ✓ Manufacturing under (CE) Certificate

BASIC UNIT INCLUDE

- ✓ P150 Air Plasma Torch x 5mtr
- ✓ Earth Clamp c/w cable
- ✓ Owner Instruction Book

PARAMETERS

	Adjustment range	Preset
Input power voltage (V)	AC415V±15% 3PH	
Input voltage frequency (HZ)	50/60	
Rated input power capacity(KVA)	29.2	
No-load voltage (V)	307	
Output current range (A)	5-160	
Pre-flow(S)	0.1-5	0.2
Post-gas(S)	0-30	5
Motor generator requirements for full arc stretch at full output (KW)	60	
Recommended cut capacity(mm)	45	
Severance capacity(mm)	60	
Duty cycle (%)	60	
Weight (KG)	45	
Dimension (mm)	622×280×480	

Website: www.dynaweld.com.my

Email : marketing@dynaweld.com.my

Contact: +603-83227661

Fax : +603-83251665