MODEL : MMA400I

Dynaweld 400I Inverter DC MMA Welding Machine





ADVANTAGES

- √ Compact design
- √ Auto-protection
- √ Unique air duct design
- √ Manufacturing under (CE) Certificate
- √ 1 year warranty
- √ VRD SAFETY SWITCH
  -Built-in Voltage Reduction Device with ON/OFF toggle for enhanced operator protection

Standard Accessory

- Dinse plug 50-70mm (2pcs)

Model	MMA400I
Input Power Voltage (V)	AC415V±15%, 3PH
Input Voltage Frequency (Hz)	50/60
Rated Input Power Capacity (KVA)	18.2
Rated Input Current (A)	27.6
No-load Voltage (V)	67.5
Output Current Range (A)	30-400
Rated Output Voltage (V)	36
Duty Cycle (%)	60
Insulation Class	F
Protection Class	IP21S
Electrode size (mm)	2.5-5.0
Power Factor	0.93
Efficiency (%)	85
Weight (KG)	15.5
Dimension (mm)	450x220x343

DYNAWELD SDN BHD 200701004518 (762517-P)
No 12A, Jalan PP 11/5, Alam Perdana Industrial Park,
Taman Putra Perdana, 47130, Puchong, Selangor.
Email : marketing@dynaweld.com.my Website : www.dynaweld.com.my
Tel : +603-8322 7661 Fax : +603-8325 1665