



Pro-Evo MIG280

The "Maxxi Korea" Pro-EvoMIG 280 is a New Technology design MIG welding power source has a broad welding ampere range of 20-270amp. It designed in slimly Body with container space on top to keep all the using consumables. At the weight of 21kgs, Single Phase (380/415volt) and Duty Cycle of 60%, you have more portability to take to the most demanding and highest quality job.

ADVANTAGES

- ✓ Well protected internally
- ✓ Smart Design
- ✓ High Duty Cycle (60%)
- ✓ Outstanding stability & performance
- ✓ Manufacturing under (CE) Certificate

BASIC UNIT INCLUDE

- ✓ 3 meter MIG Torch
- ✓ Earth Clamp c/w cable & 35-50mm dinse plug
- ✓ Co2 gas regulator
- ✓ Owner Instruction Book

PARAMETERS

	MMA	MIG
Input power voltage (V)	AC380V±15% 3PH	
Rated input power capacity (KVA)	9.4	10.6
Frequency (HZ)	50/60	
Rated input current (A)	14.2	16
No-load voltage (V)	54	
Output current range (A)	20-270	20-270
No-load consumption (W)	60	
Duty cycle (%)	60	
Efficiency (%)	85	
Power factor	0.93	
Insulation class	F	
Protection class	IP21S	
Electrode / Wire size (mm)	0.6-1.2	
Weight (kg)	21	
Dimension (mm)	622x280x450	

Website: www.dynaweld.com.my

Email : marketing@dynaweld.com.my

Contact: +603-80630838

Fax : +603-80680538