



TIG 300P+c

This TIG 300P+c is a Latest Technology which has a broad welding amperage range. Then through voltage reducing-rectifying-wave filtering as well as its pulse-width modulation (pwm) and closed-loop back circuit control technology to output the stable DC current. Our machine is packed with innovative unique features with fine voltage tuning adjustment for the flexibility of the different welding application.

ADVANTAGES

- ✓ Advance Inverter Technology
- ✓ Adjustable Arc Force Supports
- ✓ Compact and Portable
- ✓ Advance HF arc-striking with easy
- ✓ Manufacturing under (CE) Certificate

BASIC UNIT INCLUDE

- ✓ WP26 TIG Torch 3/8" Fitting
- ✓ Argon Regulator
- ✓ Earth Clamp with Cable
- ✓ Owner Instruction Book

PARAMETERS

	MMA	TIG	COLD TIG
Input power voltage (V)	AC240V±15% 1PH		
Rated input power capacity(KVA)	11	8.4	
Rated output voltage (V)	31.2	22	
Rated input current (A)	50	38.2	
No-load voltage (V)		62	
Output current range (A)	30-280	10-200	
Post-gas time (S)		2-9.9	
Pre -flow time (S)		0.0-1	
No-load consumption (W)		60	
Pulse current (A)		10-300	
Slope -down time (S)		0-9.9	
Pulse frequency (HZ)		0.1-30	
Pulse width (%)		5-90	
Welding current (ms)			10-200
Welding interval (ms)			200-999
Duty cycle (%)		60	
Efficiency (%)		85	
Power factor		0.93	
Insulation class		F	
Weight (kg)		14.5	
Dimension (mm)		450x220x345	

Website: www.dynaweld.com.my
Email : marketing@dynaweld.com.my
Contact: +603-83227661
Fax : +603-83251665