







Pro-Evo ARC 2600

"Maxxi Korea" Pro-EvoARC2600 is a Latest Technology which has a broad welding amperage range of 30-260amp. It is design with single phase (230V), so that you can perform and is portable at job sites. It is also design to wpr with all electrode types wit adjustable arc force support for easier arc striking, and It has Auto-protection against over voltage and over heat..

ADVANTAGES

V Advance Inverter Technology

V Adjustable Arc Force Supports

V Compact and Portable

V Outstanding Arc Stability

V Over protection against over voltage and over heat

BASIC UNIT INCLUDE

V Dinse Plug 35-50 (2pcs) **V** Owner Instruction Book

Website: www.dynaweld.com.my

Email: marketing@dynaweld.com.my

Contact: +603-83227661 Fax : +603-83251665

PARAMETERS

Input power voltage (V)	AC230V±15%,1PH
Input voltage frequency (HZ)	50/60
Rated input power capacity (KVA)	8
Rated input current(A)	34.8
No-load voltage (V)	65
Output current range (A)	30-250
Rated output voltage (v)	28.8
Insulation Class	F
Protection Class	IP21S
Duty cycle (%)	60
Electrode Size (mm)	2.0-4.0
Weight (KG)	4.5
Dimension (mm)	356×153×225