



Pro-Evo CUT7000

The PRO-EVOCUT 7000 Inverter Compact and Combination Air Plasma Cutting machine has a broad welding ampere range of 20-70amp. The Rugged Polycarbonate body designed in Single Phase (220/230volt), heavy duty with duty cycle at 60% and the Easy Operating Function is more flexibility for deference thickness of cutting application.

ADVANTAGES

- ✓ Advance design, high inveter frequency, high duty cycle & low energy consumption.
- ✓ Portable with light weight.
- ✓ More economical & more efficient
- ✓ Auto-protection

BASIC UNIT INCLUDE

- ✓ Female connector air plasma torch.
- ✓ 200A earth clamp c/w cable
- ✓ 35-50mm dinse plug & Air filter regulator.

PARAMETERS

Input power voltage (V)	AC220V±15%,1PH
Rated input power capacity(KVA)	7.9
Input voltage frequency (HZ)	50/60
No-load voltage (V)	240
Output current range (A)	20-60
Arc striking	TOUCH
Arc pressure (M Pa)	0.6
Duty cycle (%)	60
Cutting thickness (mm)	23
Weight (KG)	18
Dimension (mm)	480x201x295

Website: www.dynaweld.com.my

Email : marketing@dynaweld.com.my

Contact: +603-80630838

Fax : +603-80680538